

PENTAX | M-60 / M-100 Series

Smart, and Accurate Hand-held Distance Meter

- **Flexible Range:**
60m (M-60) /
100m (M-100) quick laser
measurement within
3 seconds
- **Long Battery Life:**
5000 measurements with
2 AA batteries
- **Slope:**
Built in tilt sensor,
automatically detects the
slope ($\pm 45^\circ$) (M-100)
- **Smart Multi Functions:**
Built in area and volume
calculation system,
and many other functions
for a smooth workflow
- **Any Environment:**
Protection against
water and dust (IP54)



Model	M-60	M-100
Range	0.05 to 60m	0.05 to 100m
Minimum Range	1mm	
Measuring Accuracy	±2mm	
Measuring Time	Within 3 seconds	
Slope	Circulator Vial	Tilt sensor
Slope Accuracy	—	±3°
Slope Range	—	±45°
Battery	AA battery x2	
Battery Life	Approximately 5000 Individual measurements (Alkaline)	
Environment	IP54 Water and dust resistant	
Safeguard Systems	Auto power off	
	Alarm display for remaining battery	
	Alarm display for temperature	
Operating Temperature	0°C ~ 40°C	
Weight	100g	150g
Other Systems	Area calculating	
	Volume calculation	
	Continuous measurement	
	Height measurement	
	Addition/Subtraction	
	Maximum/Minimum measurement	
	Saving measurement result to storage	
		Horizontal distance conversion

* Specifications are subject to change without notice

TI Asahi Co., Ltd.
International Sales Department
 4-3-4 Ueno Iwatsuki-Ku, Saitama-Shi
 Saitama, 339-0073 Japan
 Tel.: +81-48-793-0118
 Fax: +81-48-793-0128
 E-mail: International@tiasahi.com

www.pentaxsurveying.com/en/

Your Official Pentax Dealer



The CE marking assures that this product complies with the requirements of the EC directive for safety.

JSIMA
 Japan Surveying Instruments Manufacturers' Association

Member symbol of the Japan Surveying Instruments Manufacturers' Association representing the high quality surveying products.

